



WORK[®]
INDUSTRIA ARGENTINA

UPS



**UPS LYONN
ULT 1000 VT a 10000 VRM**



www.estabilizadoreswork.com.ar

WORK[®]

Lider en Energía Confiable



WORK[®]
INDUSTRIA ARGENTINA

✉ info@estabilizadoreswork.com.ar

📍 Quirno Costa 35 Témperey

☎ 011 4264-8841 / 011 3979-1694

UPS ULT 1000 a 10000 VRM

El modelo UPS ULT VRM para montaje en rack viene en diferentes alturas como 1RU, 2 RU o 3 RU, para satisfacer las diferentes demandas de espacio.

Las UPS UPS ULT VRM para montaje en rack están disponibles desde 700 VA -19" hasta 6 KVA.

La serie LYONN Rackeable en 19" está diseñada para ser flexibles y para encajar en distintos espacios.

El panel de control puede ser removido y colocado en la posición mas conveniente, vertical u horizontal.

El panel de control puede ser sacado del panel frontal y conectado al panel trasero para posibilitar el comando cableado remoto del equipo.

MODELO TOWER MODELO RACKEABLE	ULT VT 1K ULT VRM RACK	ULT VT 1.5K ULT VRM RACK	ULT VT 2K ULT VRM RACK	ULT VT 3K ULT VRM RACK	ULT VT 6K ULT VRM RACK	ULT VT 8K ULT VRM RACK	ULT VT 10K ULT VRM RACK	
PHASE	Single phase with ground							
CAPACITY	1000VA/800W	1500VA/1200W	2000VA/1600W	3000VA/2400W	6000VA/4800W	8000VA/6400W	10000VA/8000W	
INPUT	Voltage Range - Low Line Transfer	160 VAC ± 5% or 80 VAC ± 5% @ 100% load			176 VAC ± 3% @ 100% load			
	Voltage Range - Low Line Comeback	175 VAC ± 5% or 85 VAC ± 5% @ 100% load			186 VAC ± 3% @ 100% load			
	Voltage Range - High Line Transfer	300 VAC ± 5% or 150 VAC ± 5%			300 VAC ± 3%			
	Voltage Range - High Line Comeback	290 VAC ± 5% or 145 VAC ± 5%			290 VAC ± 3%			
	Frequency Range	40 Hz - 70 Hz			46 - 54 Hz or 56 - 64 Hz			
	Power Factor	≥0.99 @ Nominal Voltage (Full load)			≥0.99 @ 100% load			
OUTPUT	Output Voltage	208/220/230/240 VAC			208/220/230/240 VAC			
	AC Voltage Regulation (Batt. Mode)	± 3%			± 1%			
	Frequency Range (Synchronized Range)	47-53 Hz or 57-63 Hz			46 - 54 Hz or 56 - 64 Hz			
	Frequency Range (Batt. Mode)	50 Hz ± 0.25 Hz or 60Hz ± 0.3 Hz			50 Hz ± 0.1 Hz or 60 Hz ± 0.1 Hz			
	Current Crest Ratio	3:1			3:1			
	Harmonic Distortion	≤3 % THD (Linear Load) ≤6 % THD (Non-linear Load)	≤4 % THD (Linear Load) ≤7 % THD (Non-linear Load)		≤3 % THD (Linear Load) ≤6 % THD (Non-linear Load)			
	TransferTime - AC Mode to Batt. Mode Inverter to Bypass	4 ms (Typical)			Zero			
	Waveform (Batt. Mode)	Pure Sinewave			Zero			
	EFFICIENCY	AC Mode	85%		88%		89%	
		Battery Mode	83%		88%		88%	
BATTERY	Standard Model - Battery Type	12 V / 7 Ah	12 V / 9 Ah	12 V / 7 Ah	12 V / 9 Ah	12 V / 7 Ah	12 V / 9 Ah	
	Standard Model - Numbers	3	3	6	6	20	20	
	Standard Model - Typical Recharge Time	4 hours recover to 90% capacity			7 hours recover	8 hours recover	9 hours recover	
	Standard Model - Charging Current (max.)	1.0 A			1.0 A			
	Standard Model - Charging Voltage	41.0 VDC ± 1%		82.1 VDC ± 1%		273.0 VDC ± 1%		
	Long-run Model - Battery Type	Depending on applications			Depending on applications			
	Long-run Model - Numbers	3	3	6	6	18-20	18-20	
Long-run Model - Charging Current (max.)	8.0 A			4.0 A				
Long-run Model - Charging Voltage	41.0 VDC ± 1%		82.1 VDC ± 1%		273.0 VDC ± 1%			
INDICATORS	LCD Display UPS status, Load level, Battery level, Input/Output voltage, Discharge timer, and Fault conditions							
ALARM	Battery Mode	Sounding every 4 seconds						
	Low Battery	Sounding every second						
	Overload	Sounding twice every second						
	Fault	Continuously sounding						
PHYSICAL	Stand. Model - Dimension, D x W x H(mm)	397 x 145 x 220		421 x 190 x 318		592 x 250 x 576		
	Stand. Model - Net Weight (kgs)	13	14	26	28	81	83	
	Long-run Model - Dimension, D x W x H(mm)	397 x 145 x 220		421 x 190 x 318		592 x 250 x 576		
	Long-run Model - Net Weight (kgs)	7	7	13	13	25	27	
PHYSICAL	Stand. Model - Dimension, D x W x H(mm)	420 x 438 x 88 [2U]		580 x 438 x 133 [3U]		UPS Unit : 580x438x133 [3U] Battery Pack: 580x438x133 [3U]	UPS Unit : 580x438x133 [3U] Battery Pack: 580x438x133 [3U]	
	Stand. Model - Net Weight (kgs)	16	17	29	31	UPS Unit: 17 Battery Pack: 57	UPS Unit: 17 Battery Pack: 57	
	Long-run Model - Dimension, D x W x H(mm)	420 x 438 x 88 [2U]		580 x 438 x 133 [3U]		580 x 438 x 133 [3U]	580 x 438 x 133 [3U]	
	Long-run Model - Net Weight (kgs)	10	10	17	17	17	17	
ENVIRONMENT	Humidity	20-90 % RH @ 0- 40°C (non-condensing)						
	Noise Level	Less than 45dB @ 1 Meter			Less than 55dB @ 1Meter		Less than 58dB @ 1 Meter	
MANAGEMENT	Smart RS-232 / USB	Supports Windows2 2000/2003/XP/Vista/2008, Windows2 7, Linux, Unix, and MAC						
	Optional SNMP	Power management from SNMP manager and web browser						

*Derate to 60% of capacity in Frequency converter mode and to 80% when the output voltage is adjusted to 208VAC. ** L means long-run model

Lider en Energia Confiable